NIGHTHAWK-BTXTM

Most Advanced Version of Viken's Handheld X-Ray Backscatter Imaging System







MULTI MODALITY

SAFELY EVOLVED


Targeted x-ray shielding leverages every photon for optimized image quality without increasing x-ray tube voltage/power or additional scatter/exposure to operator.

EXTENDED DETECTOR

Largest backscatter detector collection area of the Nighthawk family provides highest quality imaging even at a standoff distance. Ideal for large FOV scans and for increasing sensitivity though thick materials.

SEE DEEPER & DARKER


Improved penetration and resolution provide crisp clear visualization of concealed objects even behind thick steel.



+KEY UPGRADES

Featured

Pb TRAP DETECT - Don't second guess the results.
True XRF technology automatically identifies lead traps alerting user to hidden materials during Bx or Tx scans.









+PERFORMANCE IMAGING TOOLS

BROADWING-DTX - Quick connect on the fly dynamic Tx imaging. See what you've been missing without missing a beat. Fits in places traditional panels cannot. Avoid panel setup and positioning time.



The **NIGHTHAWK-BTX** is the only series compatible with **BROADWING-DTX**. Request a datasheet for more details.

WINGBAR-RGD TABLET WINGBAR-RGD 4G TABLET

+SUPPLEMENTAL ACCESSORIES

- TACTICAL BACKPACK
- SUNSHIELD
- SPARE BATTERY PACK
- 1, 2, 4, AND 6-BAY CHARGERS



For more information on Nighthawk-BTX™ contact us at sales@vikendetection.com

NIGHTHAWK-BTXTM

COMMON NIGHTHAWK-BTX™ SPECIFICATIONS

All versions of the Nighthawk-BTX series scanners include the following standard options:

BATTERIES	14.4V (YELLOW) Battery Pack 120 kV = 4-6 hours 140 kV = 3-5 hours at typical duty cycles	CAMERA	5MP Color Front Facing Camera	
		SCANS	Up to 16in (41cm) / s Max Scan 30s	
DISPLAY	6in High Resolution Color Touch LCD	SAFETY	Configurable Single/Dual Trigger Modes Top, Side, and Front X-ray Indicator Lights X-Ray Beam Arming Interlocks Front Facing Flashlight Dual X-ray Demarcation Lasers	
OPERATING CONDITIONS	-4°F (-20°C) to 140°F (60°C)			
CONNECT	Wireless IEEE 802.11 & 802.15.1 GPS USB-C Dual Front Accessory Interfaces 4G/5G Compatible with Hotspot*	SYSTEM	Android Based Application	
		COMPLIANCE	ROHS CE (pending)	
		STANDARD ACCESSORIES	Lockable Rolling Weatherproof Case Adjustable Safety Strap System Check Shield 2x Battery Packs	
IMAGING	5 Color Viewing Modes Automatic Contrast Optimization Manual Contrast Adjust Image Annotation Suspicious Image Flag 4 Image Enhancement Filters	ACCECCATIES	110/220V AC 1-Bay Battery Charger Interface Cable User Guide	
		SUPPORT	Complimentary Software Updates Training Services Available Extended Warranty Available	

^{*}Hotspot / Cellular plan not provided by Viken.

MODEL SPECIFIC SPECIFICATIONS

MODELS	NHBTX-120W5	NHBTX-120W7	NHBTX-140W7A	NHBTX-140W7B	NHBTX-140W10
TUBE	120kV / 5W	120kV / 7W	140k\	/	140kV / 10W
DIMENSIONS	W=282 / H=199 / L=265 [mm]		W=282 / H=199 / L=278 [mm]		
WEIGHT*	9.5 lb [4.3kg]	10.7lb [4.8 kg]	10.7lb [4.8 kg]	10.7lb [4.8 kg]	10.7lb [4.8kg]
PENETRATION	6.5 mm	7 mm	8.5 mm	8.5 mm	10 mm


^{*}Dimensions of scanner enclosure. Does not include accessories or soft fittings

CONFIGURABLE OPTIONS

Customized at the factory for your needs

+Pb TRAP DETECT	Add automatic true XRF lead detection and identification
DUAL TRIGGER	Requires simultaneous 2-trigger depress to emit X-Rays
DISABLE WIRELESS	Disables WIFI/Bluetooth for EOD sensitive use cases

Additional customizations are available. Ask your sales representative for more information.





^{**}Weight includes battery. +Pb Trap detection upgrade adds 0.1lbs[.04kg].